acc. to OSHA HCS

Printing date 03/09/2016 Reviewed on 02/16/2016

### 1 Identification

- · Product identifier
- Trade name: Avesta BlueOne Pickling Paste 130
- · Application of the substance / the mixture Surface treatment of stainless and high alloyed steels
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

voestalpine Böhler Welding Nordic AB

Lodgatan 14

SE-211 24 Malmö, Sweden

Tel: +46 (0)40 - 28 83 00

Fax: +46 (0)40 - 93 94 24

www.voestalpine.com/welding

#### · Information department:

Mirna Castro

+46 (0) 40 28 83 11; Mirna. Castro @voestalpine.com

· Emergency telephone number: Tel: +44-8701906800 (English)

## 2 Hazard(s) identification

#### · Classification of the substance or mixture

Acute Tox. 2 H310 Fatal in contact with skin.

Acute Tox. 3 H331 Toxic if inhaled.

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements -
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS06

- · Signal word Danger
- Hazard-determining components of labeling:

hydrogen fluoride

nitric acid

#### · Hazard statements

Fatal in contact with skin.

Toxic if inhaled.

Causes severe skin burns and eye damage.

#### · Precautionary statements

Do not breathe vapours.

Wear protective gloves/protective clothing/eye protection/face protection.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Contd. on page 2)

Page 2/10

# Safety Data Sheet

### acc. to OSHA HCS

Printing date 03/09/2016 Reviewed on 02/16/2016

### Trade name: Avesta BlueOne Pickling Paste 130

(Contd. of page 1)

If swallowed: Rinse mouth. Do NOT induce vomiting.

Take off immediately all contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· NFPA ratings (scale 0 - 4)



Health = 3 Fire = 0 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 4 Fire = 0

Reactivity = 0

- · Other hazards The lists that were valid during the creation were used as basis.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 7697-37-2	nitric acid	12.5-25%	
EINECS: 231-714-2	<ul> <li>♠ Ox. Liq. 3, H272</li> <li>♠ Met. Corr.1, H290; Skin Corr. 1A, H314</li> </ul>		
CAS: 7664-39-3	hydrogen fluoride	5-12.5%	
EINECS: 231-634-8	Acute Tox. 2, H300; Acute Tox. 1, H310; Acute Tox. 2, H330  Met. Corr.1, H290; Skin Corr. 1A, H314		

· nonhazardous components:

Inorganic binder 5-15 % Water Rest

### 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

Seek medical treatment.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek immediate medical advice.

(Contd. on page 3)

Page 3/10

# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/09/2016 Reviewed on 02/16/2016

Trade name: Avesta BlueOne Pickling Paste 130

(Contd. of page 2)

After rinsing with water. Rub in Ca-gluconate solution or Ca-gluconate gel immediately. If available rinse with Avesta First Aid spray or Hexafluorine instead of water.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Do not induce vomiting; immediately call for medical help.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

Seek medical treatment.

- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Suitable to surrounding conditions
- · Special hazards arising from the substance or mixture

Nitrogen oxides (NOx)

Sulphur dioxide (SO2)

Hydrogen fluoride (HÉ)

- · Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear fully protective suit.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Use respiratory protective device against the effects of fumes/dust/aerosol.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Pick up mechanically.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Ensure that suitable extractors are available on processing machines

· Information about protection against explosions and fires: The product is not flammable.

(Contd. on page 4)

Page 4/10

# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/09/2016 Reviewed on 02/16/2016

Trade name: Avesta BlueOne Pickling Paste 130

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Prevent any seepage into the ground.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed.

Store under lock and key and with access restricted to technical experts or their assistants only. Store in 5-35° C. Heat and sunlight will increase pressure and may lead to the bottle to swell.

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

· Control parameters

## · Components with limit values that require monitoring at the workplace:

#### 7697-37-2 nitric acid

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: 10 mg/m³, 4 ppm

Long-term value: 5.2 mg/m³, 2 ppm

#### 7664-39-3 hydrogen fluoride

PEL Long-term value: 3 ppm

as F

REL Long-term value: 2.5 mg/m³, 3 ppm

Ceiling limit value: 5\* mg/m3, 6\* ppm

\*15-min, as F

TLV Long-term value: 0.41 mg/m³, 0.5 ppm

Ceiling limit value: 1.64 mg/m³, 2 ppm

as F; Skin, BEI

## · Ingredients with biological limit values:

#### 7664-39-3 hydrogen fluoride

BEI 3 mg/g creatinine

Medium: urine Time: prior to shift

Parameter: Fluorides (background, nonspecific)

10 mg/g creatinine

Medium: urine Time: end of shift

Parameter: Fluorides (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

(Contd. on page 5)

acc. to OSHA HCS

Printing date 03/09/2016 Reviewed on 02/16/2016

Trade name: Avesta BlueOne Pickling Paste 130

(Contd. of page 4)

### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Filter B

Filter B
Filter P2

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Heat protection gloves (non-combustible)

### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Face protection

### · Body protection:

Protective work clothing

Acid resistant protective clothing

Wear hand, head, and body protection which help to prevent injury from radiation, sparks, and electrical shock. See ANSI Z49.1. At a minimum this includes welder's gloves and a protective face shield, and may include arm protectors, aprons, hats, shoulder protection, and well as dark substantial clothing. Train the welder not to touch live electrical parts and to insulate himself from work and ground.

### 9 Physical and chemical properties

Information on basic physical and	chemical properties	
General Information		
Appearance:		
Form:	Pasty	
Color:	Blue	
Odor:	Pungent	
Odor threshold:	Not determined.	
pH-value at 20 °C (68 °F):	0	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	

(Contd. on page 6)

## voestalpine Böhler Welding

Page 6/10

# Safety Data Sheet

acc. to OSHA HCS

Printing date 03/09/2016 Reviewed on 02/16/2016

Trade name: Avesta BlueOne Pickling Paste 130

(Contd. of page 5)

Water: Fully miscible.

Partition coefficient (n-octanol/water): Not determined.
Dynamic at 20 °C (68 °F): 10000 mPas
Kinematic: Not determined.

· Organic solvents: 0.0 %

· Other information No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· Possibility of hazardous reactions

Reacts with various metals.

Develops corrosive gases / fumes.

When diluting, always add acid to water, never vice versa.

Reacts with alkali and metals.

- · Conditions to avoid Attacks materials containing glass and silicate.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Nitrogen oxides Hydrogen fluoride

Nitrogen oxides (NOx)

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

7664-39-3 hydrogen fluoride

Oral LD50 1276 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

acc. to OSHA HCS

Printing date 03/09/2016 Reviewed on 02/16/2016

Trade name: Avesta BlueOne Pickling Paste 130

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential Not known to be bioaccumulative
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must be specially treated adhering to official regulations.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

### 14 Transport information

· DOT, ADR, IMDG, IATA	UN2922
· UN proper shipping name	
· DOT, IATA	Corrosive liquids, toxic, n.o.s. (Hydrofluoric acid, Nitric acid)
· ADR	2922 Corrosive liquids, toxic, n.o.s. (Hydrofluoric acid, Nitric acid)
· IMDG	CORROSIVE LIQUID, TOXIC, N.O.S. (HYDROFLUORIC ACID, NITRIC ACID)
	(Contd. on page 9)

(Contd. on page 8)

acc. to OSHA HCS

Reviewed on 02/16/2016 Printing date 03/09/2016

Trade name: Avesta BlueOne Pickling Paste 130

(Contd. of page 7) · DOT · Class 8 Corrosive substances · Label 8, 6.1 · ADR · Class 8 Corrosive substances · Label 8+6.1 · IMDG · Class 8 Corrosive substances · Label 8/6.1 · Class 8 Corrosive substances · Label 8 (6.1) · Packing group · DOT, ADR, IMDG, IATA II· Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Corrosive substances · Danger code (Kemler): 86 · EMS Number: F-A,S-B Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: Not dangerous according to the above specifications. · ADR · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · IMDG · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

acc. to OSHA HCS

Printing date 03/09/2016 Reviewed on 02/16/2016

Trade name: Avesta BlueOne Pickling Paste 130

(Contd. of page 8)

· UN "Model Regulation":

UN 2922 CORROSIVE LIQUIDS, TOXIC, N.O.S. (HYDROFLUORIC ACID, NITRIC ACID), 8 (6.1), II

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

7697-37-2 nitric acid

· Section 313 (Specific toxic chemical listings):

7697-37-2 nitric acid

· TSCA (Toxic Substances Control Act):

7697-37-2 nitric acid

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS06

- · Signal word Danger
- · Hazard-determining components of labeling:

hydrogen fluoride

nitric acid

· Hazard statements

Fatal in contact with skin.

Toxic if inhaled.

Causes severe skin burns and eye damage.

(Contd. on page 10)

acc. to OSHA HCS

Printing date 03/09/2016 Reviewed on 02/16/2016

Trade name: Avesta BlueOne Pickling Paste 130

(Contd. of page 9)

#### · Precautionary statements

Do not breathe vapours.

Wear protective gloves/protective clothing/eye protection/face protection.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If swallowed: Rinse mouth. Do NOT induce vomiting.

Take off immediately all contaminated clothing and wash it before reuse.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Training hints -
- · Department issuing SDS: QHES
- · Contact: Mirna Castro
- Date of preparation / last revision 03/09/2016 / 1
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of

Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

TRGS: Technische Regeln für Gefahrstoffe (Technical Rules for Dangerous Substances, BAuA, Germany)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Ox. Liq. 3: Oxidising Liquids, Hazard Category 3

Met. Corr.1: Corrosive to metals, Hazard Category 1

Acute Tox. 2: Acute toxicity, Hazard Category 2

Acute Tox. 1: Acute toxicity, Hazard Category 1 Acute Tox. 3: Acute toxicity, Hazard Category 3

Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

\* Data compared to the previous version altered.