



A CSW Industrials Company

SAFETY DATA SHEET

Issuing Date 03-Mar-2014

Revision Date 31-Jan-2018

Revision Number 6



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name Jet-Lube® KOPR-KOTE® - Aerosol

Other means of identification

Product Code(s) 10041

(M)SDS Number WPS-JLI-093NA

Synonyms KOPR-KOTE® - Aerosol

Recommended use of the chemical and restrictions on use

Recommended Use Lubricants, Greases and Release Products

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Identification Jet-Lube LLC

Address Jet Lube LLC
930 Whitmore Drive
Rockwall, Texas USA 75087

Telephone US Office: Phone:+1-972-771-1000 Fax:+1-972-722-2108

E-mail Sales@jetlube.com

Emergency telephone number

Company Emergency Phone Number Toll Free: 1-888-771-7775

Emergency Telephone Number CHEMTREC: +1-703-527-3887 (INTERNATIONAL)
1-800-424-9300 (NORTH AMERICA)

2. HAZARDS IDENTIFICATION

Classification

Serious eye damage/eye irritation	Category 2
-----------------------------------	------------



Specific target organ toxicity (single exposure)	Category 3
Flammable Aerosols	Category 1
Gases Under Pressure	Compressed Gas

Appearance Copper Bronze

Physical state Aerosol

Odor Petroleum

GHS Label elements, including precautionary statements

Danger

Hazard statements

- May be harmful if swallowed
- Causes serious eye irritation
- May cause drowsiness or dizziness
- Extremely flammable aerosol
- Contains gas under pressure; may explode if heated



Precautionary Statements - Prevention

- Wash face, hands and any exposed skin thoroughly after handling
- Wear eye/face protection
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- Do not spray on an open flame or other ignition source
- Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor if you feel unwell

Precautionary Statements - Storage

- Protect from sunlight. Store in a well-ventilated place
- Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other information

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture**Synonyms** KOPR-KOTE® - Aerosol

Chemical Name	CAS-No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Lubricating greases A complex combination of hydrocarbons having carbon numbers predominantly in the range of C12 through C50. may contain organic salts of alkali metals, alkaline earth metals, etc.	74869-21-9	45-50	-	-
Copper (flake)	7440-50-8	5-10	-	-
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	1-5	-	-
Molybdenum (IV) sulfide	1317-33-5	1-5	-	-

4. FIRST AID MEASURES

First aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	In case of contact with liquefied gas, thaw frosted parts with lukewarm water.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed**Symptoms** No information available.**Indication of any immediate medical attention and special treatment needed****Note to physicians** Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray.
Unsuitable extinguishing media	DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Ruptured cylinders may rocket.
Hazardous Combustion Products	Carbon oxides.
Explosion Data	
Sensitivity to Mechanical Impact	Yes.
Sensitivity to Static Discharge	Yes.
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Contents under pressure. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
Other Information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions	See Section 12 for additional Ecological Information.
----------------------------------	---

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other
--------------------------------	--

ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Copper (flake) 7440-50-8	TWA: 0.2 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume	
Molybdenum (IV) sulfide 1317-33-5	TWA: 10 mg/m ³ Mo inhalable particulate matter TWA: 3 mg/m ³ Mo respirable particulate matter	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ Mo	IDLH: 5000 mg/m ³ Mo	
Chemical Name	Alberta	British Columbia	Ontario TWAEV	Quebec
Copper (flake) 7440-50-8	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³	TWA: 1 mg/m ³ TWA: 0.2 mg/m ³	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³	TWA: 0.2 mg/m ³ TWA: 1 mg/m ³
Molybdenum (IV) sulfide 1317-33-5	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 3 mg/m ³ TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Hand protection

Impervious gloves. Wear suitable gloves.

Skin and body protection

Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.



General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Aerosol
Appearance	Copper Bronze
Odor	Petroleum
Color	No information available
Odor Threshold	No data available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	7		
Melting / freezing point	260 °C	None known	
Boiling point / boiling range	316 °C	None known	
Flash Point	> 75 °C	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air		None known	
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Relative density	0.881		
Water Solubility	Insoluble in water		
Solubility(ies)	No data available	None known	
Partition coefficient: n-octanol/water	Not Applicable		
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No information available		
Oxidizing properties	No information available		

Other Information

Softening Point	No information available
Molecular Weight	No information available
VOC Content (%)	No information available
264	
Liquid Density	No information available
Bulk Density	No information available
Particle Size	No information available
Particle Size Distribution	No information available

10. STABILITY AND REACTIVITY

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.

Conditions to avoid	Heat, flames and sparks. Excessive heat.
Incompatible materials	None known based on information supplied.
Hazardous Decomposition Products	Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. Causes eye irritation.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation.
Ingestion	Specific test data for the substance or mixture is not available.

Information on toxicological effects

Symptoms No information available.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 2,280.00 mg/kg

Unknown acute toxicity No information available

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	Inhalation LC50
Lubricating greases A complex combination of hydrocarbons having carbon numbers predominantly in the range of C12 through C50. may contain organic salts of alkali metals, alkaline earth metals, etc.	= 2280 mg/kg (Rat)		
Solvent naphtha (petroleum), medium aliphatic	> 25 mL/kg (Rat)	> 3000 mg/kg (Rabbit)	> 13 mg/L (Rat) 4 h
Molybdenum (IV) sulfide			> 2820 mg/m ³ (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. May cause skin irritation.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Irritating to eyes.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Legend	

Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	No information available.

12. ECOLOGICAL INFORMATION

Marine Pollutant This product contains a chemical which is listed as a severe marine pollutant according to DOT

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Lubricating greases A complex combination of hydrocarbons having carbon numbers predominantly in the range of C12 through C50. may contain organic salts of alkali metals, alkaline earth metals, etc.	>1001 mg/l	96h LC50: > 2000 mg/L (Salmo gairdneri)	-	
Copper (flake)	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: < 0.3 mg/L (Pimephales promelas) 96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: = 0.2 mg/L (Pimephales promelas) 96h LC50: = 0.3 mg/L (Cyprinus carpio) 96h LC50: = 0.112 mg/L (Poecilia reticulata) 96h LC50: = 0.8 mg/L (Cyprinus carpio) 96h LC50: = 1.25 mg/L (Lepomis macrochirus)	-	48h EC50: = 0.03 mg/L
Solvent naphtha (petroleum), medium aliphatic	96h EC50: = 450 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 800 mg/L (Pimephales promelas)	-	48h EC50: > 100 mg/L

Persistence and Degradability No information available.

Bioaccumulation

Mobility No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number D001

California Hazardous Waste Codes 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Copper (flake) 7440-50-8	Toxic

14. TRANSPORT INFORMATION

DOT

UN-No. UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1
Marine Pollutant This product contains a chemical which is listed as a severe marine pollutant according to DOT
Description UN1950, Aerosols, flammable, 2.1
Emergency Response Guide Number 126

TDG

UN Number UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Packing Group None
Marine Pollutant This product contains a chemical which is listed as a severe marine pollutant according to TDG.
Description UN1950, Aerosols, 2.1

MEX

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2.2
Description UN1950, Aerosols, 2.2

ICAO

UN-No. UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Description UN1950, Aerosols, 2.1

IATA

UN Number UN1950
Proper Shipping Name Aerosols, flammable



Hazard Class	2.1
Packing Group	None
ERG Code	10L
Description	UN1950, Aerosols, flammable, 2.1

IMDG

UN Number	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1
Packing Group	None
EmS-No.	F-D, S-U
Description	UN1950, Aerosols, 2.1, FP >75C

RID

UN-No.	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1
Classification code	5F
Description	UN1950 Aerosols, 2.1,
ADR/RID-Labels	2.1

ADR

UN-No.	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2.1
Classification code	5F
Tunnel restriction code	(D)
Description	UN1950 Aerosols, 2.1,

ADN

UN-No.	UN1950
Proper Shipping Name	Aerosols
Hazard Class	2
Classification code	5F
Special Provisions	190, 327, 344, 625
Description	UN1950, Aerosols, 2.1
Hazard Labels	2.1
Limited Quantity	1 L
Ventilation	VE01, VE04

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

Ozone-depleting substances (ODS) Not applicable

Persistent Organic Pollutants Not applicable

Export Notification requirements Not applicable

International Inventories

TSCA	Complies.
DSL/NDSL	Contact supplier for inventory compliance status.
EINECS/ELINCS	Complies.
ENCS	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AICS	Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS-No	Weight-%	SARA 313 - Threshold Values %
Copper (flake) - 7440-50-8	7440-50-8	5-10	1.0

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden release of pressure hazard	Yes
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper (flake) 7440-50-8		X	X	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper (flake) 7440-50-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Copper (flake) 7440-50-8	X	X	X	X	X
Molybdenum (IV) sulfide 1317-33-5		X			



16. OTHER INFORMATION

NFPA	Health hazards 2	Flammability 4	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2*	Flammability 4	Physical hazards 0	Personal Protection X

*Chronic Hazard Star Legend*** = Chronic Health Hazard*

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 03-Mar-2014

Revision Date 31-Jan-2018

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet