

# PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown

**LA-CO Industries, Inc.**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)  
Date of issue: 07/28/2015  
Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
Trade name : PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Paint.

### 1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.  
1201 Pratt Boulevard  
Elk Grove Village, IL. 60007-5746  
Phone: (847) 956-7600  
Fax: (847) 956-9885  
E-mail: customer\_service@laco.com



### 1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification in accordance with the Globally Harmonized Standard

Flam. Liq. 3 H226  
Repr. 2 H361

Full text of classification categories and H statements : see section 16

### 2.2. Label elements

#### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02



GHS08

Signal word (GHS-US) : Warning  
Hazard statements (GHS-US) : H226 - Flammable liquid and vapour  
H361 - Suspected of damaging fertility or the unborn child  
Precautionary statements (GHS-US) : P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, open flames, sparks. - No smoking  
P233 - Keep container tightly closed  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical, lighting, ventilating equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P280 - Wear protective gloves  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P308+P313 - If exposed or concerned: Get medical advice/attention  
P370+P378 - In case of fire: Use Suitable extinguishing media to extinguish  
P403+P235 - Store in a well-ventilated place. Keep cool  
P405 - Store locked up  
P501 - Dispose of contents/container to an authorised waste collection point

# PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	% (w/w)	GHS-US classification
tert-butyl acetate	(CAS No) 540-88-5	33.42 – 33.59 White 46.97 – 47.21 Blue 44.32 – 44.55 Green 39.24 – 39.44 Orange 51.75 – 52.01 Light Green 29.85 – 30 Pink 36.58 – 36.76 Purple 42.63 – 42.85 Brown	Flam. Liq. 2, H225
Cyclohexanone	(CAS No) 108-94-1	9.81 Blue 5.29 Pink	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332
Butyl acetate	(CAS No) 123-86-4	3.13 – 3.85 White 2.39 – 3.15 Blue 3.31 – 4.04 Green 3.58 – 4.37 Orange 2.5 – 3.06 Light Green 3.3 – 4.11 Pink 4.01 – 4.96 Purple 3.41 – 4.21 Brown	Flam. Liq. 3, H226 STOT SE 3, H336
2-methoxy-1-methylethyl acetate	(CAS No) 108-65-6	0.68 – 1.37 White 2.1 – 4.19 Blue 0.49 – 0.98 Green 0.56 – 1.12 Orange 0.47 – 0.93 Light Green 1.13 – 2.27 Pink 1.05 – 2.1 Purple 0.87 – 1.74 Brown	Flam. Liq. 3, H226
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%)	(CAS No) 2786-76-7	1.2 Orange 1.43 Pink 3.68 Brown	Skin Sens. 1, H317
Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%)	(CAS No) 64742-48-9	3 – 3.02 White 2.38 – 2.39 Blue 2.97 – 2.98 Green 3.46 – 3.48 Orange 2.33 Light Green 2.33 – 2.34 Pink 2.48 – 2.49 Purple 2.61 – 2.62 Brown	Flam. Liq. 4, H227 Asp. Tox. 1, H304
Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene <0.1%)	(CAS No) 64742-95-6	0.12 – 0.6 White 0.08 – 0.41 Blue 0.13 – 0.65 Green 0.14 – 0.7 Orange 0.1 – 0.48 Light Green 0.12 – 0.62 Pink 0.15 – 0.77 Purple 0.13 – 0.65 Brown	Asp. Tox. 1, H304
1,2,4-trimethylbenzene	(CAS No) 95-63-6	0.12 – 0.6 White 0.08 – 0.41 Blue 0.13 – 0.65 Green 0.14 – 0.7 Orange 0.1 – 0.48 Light Green 0.12 – 0.62 Pink 0.15 – 0.77 Purple 0.13 – 0.65 Brown	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Aquatic Chronic 2, H411
[N,N,N',N'',N''',N'''-hexaethyl-29H,31H-phthalocyaninetrimethylamino(2-)-N29,N30,N31,N32]copper	(CAS No) 28654-73-1	0.19 – 0.44 Blue 0.02 – 0.05 Green 0.01 – 0.02 Light Green	Skin Sens. 1B, H317
2-ethylhexanoic acid, zirconium salt	(CAS No) 22464-99-9	0.16 White, Green 0.13 Blue, Purple 0.18 Orange 0.12 Light Green, Pink 0.14 Brown	Repr. 2, H361

Full text of H-statements: see section 16

# PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Get medical advice/attention if you feel unwell. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Suspected of damaging fertility or the unborn child.
-------------------	--

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: None known.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.
Reactivity	: No dangerous reactions known.

#### 5.3. Advice for firefighters

Firefighting instructions	: Eliminate all ignition sources if safe to do so. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist.
------------------	--

##### 6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable gloves.
Emergency procedures	: Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment	: Wear suitable gloves.
Emergency procedures	: Stop leak if safe to do so. Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Wipe up with absorbent material (for example cloth).
-------------------------	--

#### 6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling	: No open flames. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

# PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment.

Storage conditions : Keep container closed when not in use.

Incompatible products : Oxidizing agent. Acids. Alkali. Moisture.

Incompatible materials : Heat sources.

Heat and ignition sources : Keep away from heat, sparks and flame.

Prohibitions on mixed storage : Incompatible materials.

Storage area : Store in dry, cool, well-ventilated area.

### 7.3. Specific end use(s)

Marking.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown		
ACGIH	Not applicable	
OSHA	Not applicable	
Butyl acetate (123-86-4)		
ACGIH	ACGIH TWA (mg/m³)	713 mg/m³
ACGIH	ACGIH TWA (ppm)	150 ppm
ACGIH	ACGIH STEL (mg/m³)	950 mg/m³
ACGIH	ACGIH STEL (ppm)	200 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL (TWA) (mg/m³)	710 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	150 ppm
Canada (Quebec)	VECD (mg/m³)	950 mg/m³
Canada (Quebec)	VECD (ppm)	200 ppm
Canada (Quebec)	VEMP (mg/m³)	713 mg/m³
Canada (Quebec)	VEMP (ppm)	150 ppm
Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene <0.1%) (64742-95-6)		
ACGIH	Not applicable	
OSHA	Not applicable	
1,2,4-trimethylbenzene (95-63-6)		
ACGIH	ACGIH TWA (mg/m³)	123 mg/m³
ACGIH	ACGIH TWA (ppm)	25 ppm
OSHA	Not applicable	
Canada (Quebec)	VECD (mg/m³)	172 mg/m³
Canada (Quebec)	VECD (ppm)	35 ppm
Canada (Quebec)	VEMP (mg/m³)	123 mg/m³
Canada (Quebec)	VEMP (ppm)	25 ppm
tert-butyl acetate (540-88-5)		
ACGIH	Not applicable	
OSHA	Not applicable	
Cyclohexanone (108-94-1)		
ACGIH	ACGIH TWA (mg/m³)	50 mg/m³
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	50 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr

# PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

Cyclohexanone (108-94-1)		
OSHA	OSHA PEL (TWA) (mg/m³)	200 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
Canada (Quebec)	VEMP (mg/m³)	100 mg/m³
Canada (Quebec)	VEMP (ppm)	25 ppm
Canada (Quebec)	Notations and remarks	(Peau)
2-methoxy-1-methylethyl acetate (108-65-6)		
ACGIH	Not applicable	
OSHA	Not applicable	
Naphtha (petroleum), hydrotreated heavy (benzene < 0.1%) (64742-48-9)		
ACGIH	ACGIH TWA (mg/m³)	5 mg/m³
ACGIH	ACGIH STEL (mg/m³)	10 mg/m³
OSHA	Not applicable	
[N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyaninetrimethylamino(2-)-N29,N30,N31,N32]copper (28654-73-1)		
ACGIH	Not applicable	
OSHA	Not applicable	
2-ethylhexanoic acid, zirconium salt (22464-99-9)		
ACGIH	ACGIH TWA (mg/m³)	5 mg/m³ as Zr
ACGIH	ACGIH STEL (mg/m³)	10 mg/m³ as Zr
OSHA	Not applicable	
4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol <1%) (2786-76-7)		
ACGIH	Not applicable	
OSHA	Not applicable	

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Use rubber gloves.
Eye protection	: None under normal use.
Respiratory protection	: None under normal use.
Other information	: Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Solid marker containing liquid colored paint.
Colour	: Variable.
Odour	: Solvent.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 23 - 37.8 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available

# PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content : 67 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Open flame. Overheating. Direct sunlight. Heat. Sparks.

### 10.5. Incompatible materials

Oxidizer. Acids. Alkali. Moisture.

### 10.6. Hazardous decomposition products

May release flammable gases. Thermal decomposition generates : metallic oxides. Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Inhalation:dust,mist: Not classified.

2-ethylhexanoic acid, zirconium salt (22464-99-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 4.3 mg/l/4h
Butyl acetate (123-86-4)	
LD50 oral rat	10760 mg/kg
LD50 dermal rabbit	> 14112 mg/kg
LC50 inhalation rat (mg/l)	> 21 mg/l/4h
ATE CLP (oral)	10760.000 mg/kg bodyweight
Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene <0.1%) (64742-95-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5610 mg/l/4h
1,2,4-trimethylbenzene (95-63-6)	
LD50 oral rat	3415 mg/kg
LD50 dermal rat	3440 mg/kg
LC50 inhalation rat (ppm)	954 ppm
ATE CLP (oral)	3415.000 mg/kg bodyweight
ATE CLP (dermal)	3440.000 mg/kg bodyweight
ATE CLP (dust,mist)	1.500 mg/l/4h
tert-butyl acetate (540-88-5)	
LD50 oral rat	4100 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	4211 ppm 6 h
ATE CLP (oral)	4100.000 mg/kg bodyweight

# PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

<b>Cyclohexanone (108-94-1)</b>	
ATE CLP (dust,mist)	1.500 mg/l/4h
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LD50 oral rat	8532 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat (ppm)	4345 ppm 6 h
ATE CLP (oral)	8532.000 mg/kg bodyweight
<b>Naphtha (petroleum), hydrotreated heavy (benzene &lt; 0.1%) (64742-48-9)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5610 mg/m <sup>3</sup>
<b>[N,N,N',N'',N''',N''''-hexaethyl-29H,31H-phthalocyaninetrimethylaminato(2-)-N29,N30,N31,N32]copper (28654-73-1)</b>	
LD50 oral rat	> 10000 mg/kg
LD50 dermal rat	> 2500 mg/kg
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>	
LD50 oral rat	> 15000 mg/kg
LC50 inhalation rat (mg/l)	> 1580 mg/m <sup>3</sup> 4 h

<b>Skin corrosion/irritation</b>	: Not classified
<b>Serious eye damage/irritation</b>	: Not classified
<b>Respiratory or skin sensitisation</b>	: Not classified.
<b>Germ cell mutagenicity</b>	: Not classified
<b>Carcinogenicity</b>	: Not classified

<b>Cyclohexanone (108-94-1)</b>	
IARC group	3 - Not classifiable
<b>Reproductive toxicity</b>	: Suspected of damaging fertility or the unborn child.
<b>Specific target organ toxicity (single exposure)</b>	: Not classified
<b>Specific target organ toxicity (repeated exposure)</b>	: Not classified

<b>2-ethylhexanoic acid, zirconium salt (22464-99-9)</b>	
NOAEL (oral, rat, 90 days)	300 mg/kg bodyweight/day read across 2-ethylhexanoic acid; P-generation
<b>Aspiration hazard</b>	: Not classified
<b>Potential adverse human health effects and symptoms</b>	
Likely routes of exposure	: Inhalation;Skin and eye contact

## SECTION 12: Ecological information

### 12.1 Toxicity

<b>Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene &lt;0.1%) (64742-95-6)</b>	
LC50 fish 1	8.2 mg/l
EC50 Daphnia 1	4.5 mg/l
EC50 other aquatic organisms 1	3.7 mg/l
NOEC (acute)	0.5 mg/l
<b>1,2,4-trimethylbenzene (95-63-6)</b>	
LC50 fish 1	7.72 mg/l
LC50 other aquatic organisms 1	3.6 mg/l
EC50 other aquatic organisms 1	2.356 mg/l
<b>tert-butyl acetate (540-88-5)</b>	
LC50 fish 1	240 mg/l 96 h
EC50 Daphnia 1	410 mg/l 24 h
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
LC50 fish 1	100 - 180 mg/l
EC50 Daphnia 1	> 500 mg/l 48 h
ErC50 (algae)	> 1000 mg/l

# PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

<b>Naphtha (petroleum), hydrotreated heavy (benzene &lt; 0.1%) (64742-48-9)</b>	
LC50 fish 1	8.2 mg/l
<b>[N,N,N',N'',N''',N''''-hexaethyl-29H,31H-phthalocyaninetrimethylaminato(2-)-N29,N30,N31,N32]copper (28654-73-1)</b>	
LC50 fish 1	> 146 mg/l 96 h
EC50 Daphnia 1	> 100 mg/l 48 h
<b>2-ethylhexanoic acid, zirconium salt (22464-99-9)</b>	
LC50 fish 1	> 100 mg/l 96 h
EC50 Daphnia 1	> 0.17 mg/l 48 h
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>	
LC50 fish 1	> 500 mg/l 96 h
EC50 Daphnia 1	> 110 mg/l 48 h

### 12.2. Persistence and degradability

<b>Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene &lt;0.1%) (64742-95-6)</b>	
Persistence and degradability	Not established.
<b>tert-butyl acetate (540-88-5)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	50 % 28 d
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	89 % 10 d
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	0 % 28 d

### 12.3. Bioaccumulative potential

<b>Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene &lt;0.1%) (64742-95-6)</b>	
Bioaccumulative potential	Not established.
<b>tert-butyl acetate (540-88-5)</b>	
BCF fish 1	5.61
Log Pow	1.64
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
Log Pow	0.43
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>	
BCF fish 1	53 l/kg
Log Pow	1.28

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.

## SECTION 14: Transport information

In accordance with DOT and TDG

Transport document description	: UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, III
UN-No.(DOT)	: UN1263
Proper Shipping Name (DOT)	: Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base



# PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

Transport hazard class(es) (DOT) : 3 - Flammable liquid  
Packing group (DOT) : III - Minor Danger

### ADR

Transport document description : UN 1263 PAINT, 3, III, (D/E)  
Proper Shipping Name (ADR) : PAINT  
Packing group (ADR) : III  
Class (ADR) : 3 - Flammable liquid

### Transport by sea

UN-No. (IMDG) : UN 1263  
Proper Shipping Name (IMDG) : PAINT  
Class (IMDG) : 3 - Flammable liquids  
Packing group (IMDG) : III

### Air transport

UN-No. (IATA) : UN 1263  
Proper Shipping Name (IATA) : Paint  
Class (IATA) : 3 - Flammable Liquids  
Packing group (IATA) : III

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

<b>Butyl acetate (123-86-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
<b>2-ethylhexanoic acid, zirconium salt (22464-99-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene &lt;0.1%) (64742-95-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>1,2,4-trimethylbenzene (95-63-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>tert-butyl acetate (540-88-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Cyclohexanone (108-94-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Naphtha (petroleum), hydrotreated heavy (benzene &lt; 0.1%) (64742-48-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>[N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyaninetrimethylaminato(2-)-N29,N30,N31,N32]copper (28654-73-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### 15.2. International regulations

#### CANADA

<b>Butyl acetate (123-86-4)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
<b>Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene &lt;0.1%) (64742-95-6)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
<b>1,2,4-trimethylbenzene (95-63-6)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

# PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

<b>tert-butyl acetate (540-88-5)</b>
Listed on the Canadian DSL (Domestic Substances List) inventory.
<b>Cyclohexanone (108-94-1)</b>
Listed on the Canadian DSL (Domestic Substances List) inventory.
<b>2-ethylhexanoic acid, zirconium salt (22464-99-9)</b>
Listed on the Canadian DSL (Domestic Substances List) inventory.
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>
Listed on the Canadian DSL (Domestic Substances List) inventory.
<b>Naphtha (petroleum), hydrotreated heavy (benzene &lt; 0.1%) (64742-48-9)</b>
Listed on the Canadian DSL (Domestic Substances List) inventory.
<b>[N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyaninetrimethylaminato(2-)-N29,N30,N31,N32]copper (28654-73-1)</b>
Listed on the Canadian DSL (Domestic Substances List) inventory.
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>
Listed on the Canadian DSL (Domestic Substances List) inventory.

### EU-Regulations

<b>Butyl acetate (123-86-4)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
<b>Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (benzene &lt;0.1%) (64742-95-6)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
<b>1,2,4-trimethylbenzene (95-63-6)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
<b>tert-butyl acetate (540-88-5)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
<b>Cyclohexanone (108-94-1)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
<b>2-ethylhexanoic acid, zirconium salt (22464-99-9)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
<b>Naphtha (petroleum), hydrotreated heavy (benzene &lt; 0.1%) (64742-48-9)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
<b>[N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyaninetrimethylaminato(2-)-N29,N30,N31,N32]copper (28654-73-1)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
<b>4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (naphthol &lt;1%) (2786-76-7)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### National regulations

<b>PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown</b>
All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).
All ingredients are listed in the Toxic Substances Control Act (TSCA).
All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

# PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

### 15.3. US State regulations

#### Butyl acetate (123-86-4)

U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Pennsylvania - List of Hazardous Substances

#### tert-butyl acetate (540-88-5)


U.S. - Minnesota - Hazardous Substance List  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - New York - Right to Know List of Hazardous Chemicals  
U.S. - Pennsylvania - List of Hazardous Substances

#### Cyclohexanone (108-94-1)

U.S. - Pennsylvania - RTK (Right to Know) List  
U.S. - New York - Right to Know List of Hazardous Chemicals  
U.S. - New Jersey - Right to Know Hazardous Substance List  
U.S. - Minnesota - Hazardous Substance List

## SECTION 16: Other information

Indication of changes	: Original Document.
Data sources	: ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <a href="http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database">http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database</a> . Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <a href="http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html">http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html</a> .
Abbreviations and acronyms	: ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number. CLP: Classification, Labelling, Packaging. EC50: Environmental Concentration associated with a response by 50% of the test population. GHS: Globally Harmonized System (of Classification and Labeling of Chemicals). LD50: Lethal Dose for 50% of the test population. OSHA: Occupational Safety & Health Administration. PBT: Persistent, Bioaccumulative, Toxic. TWA: Time Weight Average. TSCA: Toxic Substances Control Act.
Other information	: None.
NFPA health hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	: 3 - Liquids and solids that can be ignited under almost all ambient conditions.
NFPA reactivity	: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



### Full text of H-statements:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Liq. 4	Flammable liquids, Category 4
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
Skin Sens. 1B	Sensitisation — Skin, category 1B

# PRO-LINE® XT PAINT MARKER White, Blue, Green, Orange, Light Green, Pink, Purple, Brown

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
according to Canadian Hazardous Products Regulations (HPR)

STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H411	Toxic to aquatic life with long lasting effects

**SDS Prepared by:** The Redstone Group, LLC  
6077 Frantz Rd.  
Suite 206  
Dublin, OH USA 43016  
T 614-923-7472  
[www.redstonegrp.com](http://www.redstonegrp.com)

LACO NA GHS SDS

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*