

PRO-WASH™ D Detergent Removable Paint Markers

LA-CO Industries, Inc.

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)
Date of issue: 08/30/2005 Revision date: 04/14/2015 Supersedes: 11/17/2008
Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Article
Trade name : PRO-WASH™ D Detergent Removable Paint Markers
Synonyms : PRO-WASH™ D Detergent Removable Paint Markers White, Yellow, Black, Blue, Green, Red

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Marking.

1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.
1201 Pratt Boulevard
Elk Grove Village, IL. 60007-5746
Phone: (847) 956-7600
Fax: (847) 956-9885
E-mail: customer_service@laco.com

1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification in accordance with the Globally Harmonized Standard

Not classified

2.2. Label elements

GHS-US labelling

No labelling applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % (w/w) | GHS-US classification |
|--|--------------------|--|--|
| ethanol | (CAS No) 64-17-5 | 43.07 White 56.6 Yellow 51 Red 53.32 Black 51.82 Blue 54.81 Green | Flam. Liq. 2, H225 |
| Isopropanol | (CAS No) 67-63-0 | 7.6 White 9.99 Yellow 9 Red 9.41 Black 9.14 Blue 9.67 Green | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| Docusate sodium USP | (CAS No) 577-11-7 | 3.89 White 3.82 Yellow 6 Red 5.87 Black 5.38 Blue 5.17 Green | Skin Irrit. 2, H315 Eye Irrit. 2A, H319 |
| 4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 | (CAS No) 2786-76-7 | 4 Red | Skin Sens. 1, H317 (Naphthol <1%) |

PRO-WASH™ D Detergent Removable Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

| Name | Product identifier | % (w/w) | GHS-US classification |
|-----------------------|----------------------|---|--|
| propyl acetate | (CAS No) 109-60-4 | 2.53 White 3.33 Yellow 3 Red 3.14 Black 3.05 Blue 3.22 Green | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336 |
| C.I. Solvent Black 29 | (CAS No) 117527-94-3 | 1.87 Black | Aquatic Chronic 2, H411 |

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water.
- First-aid measures after eye contact : If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : May cause moderate irritation.
- Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.

4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry chemical. Foam. Water spray. Water fog.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapour.
- Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

- Firefighting instructions : Cool adjacent structures and containers with water spray to protect and prevent ignition. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid all eye and skin contact and do not breathe vapour and mist.

6.1.1. For non-emergency personnel

- Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Stop the flow of material, if this is without risk.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Take up in non-combustible absorbent material and shove into container for disposal.

PRO-WASH™ D Detergent Removable Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-----------------------------------|---|
| Additional hazards when processed | : Handle empty containers with care because residual vapours are flammable. |
| Precautions for safe handling | : No open flames. No smoking. Use only non-sparking tools. Avoid all eye and skin contact and do not breathe vapour and mist. |
| Hygiene measures | : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|-------------------------------|---|
| Technical measures | : Use only non-sparking tools. |
| Storage conditions | : Keep in fireproof place. Keep container tightly closed. |
| Incompatible products | : Strong oxidizers. |
| Incompatible materials | : Heat sources. |
| Heat and ignition sources | : Keep away from heat, sparks and flame. |
| Prohibitions on mixed storage | : Keep away from incompatible materials. |
| Storage area | : Store in dry, cool, well-ventilated area. |

7.3. Specific end use(s)

Marking.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| PRO-WASH™ D Detergent Removable Paint Markers | | |
|---|------------------------|---------------------------|
| ACGIH | Not applicable | |
| OSHA | Not applicable | |
| ethanol (64-17-5) | | |
| ACGIH | ACGIH TWA (mg/m³) | 1884 mg/m³ |
| ACGIH | ACGIH TWA (ppm) | 1000 ppm |
| ACGIH | ACGIH STEL (ppm) | 1000 ppm |
| ACGIH | Remark (ACGIH) | URT irr |
| OSHA | OSHA PEL (TWA) (mg/m³) | 1900 mg/m³ |
| OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |
| Canada (Quebec) | VEMP (mg/m³) | 1880 mg/m³ |
| Canada (Quebec) | VEMP (ppm) | 1000 ppm |
| Isopropanol (67-63-0) | | |
| ACGIH | ACGIH TWA (mg/m³) | 490 mg/m³ |
| ACGIH | ACGIH TWA (ppm) | 200 ppm |
| ACGIH | ACGIH STEL (mg/m³) | 960 mg/m³ |
| ACGIH | ACGIH STEL (ppm) | 400 ppm |
| ACGIH | Remark (ACGIH) | Eye & URT irr; CNS impair |
| OSHA | OSHA PEL (TWA) (mg/m³) | 980 mg/m³ |
| OSHA | OSHA PEL (TWA) (ppm) | 400 ppm |
| Canada (Quebec) | VECD (mg/m³) | 1230 mg/m³ |
| Canada (Quebec) | VECD (ppm) | 500 ppm |
| Canada (Quebec) | VEMP (mg/m³) | 983 mg/m³ |
| Canada (Quebec) | VEMP (ppm) | 400 ppm |
| propyl acetate (109-60-4) | | |
| ACGIH | ACGIH TWA (mg/m³) | 835 mg/m³ |
| ACGIH | ACGIH TWA (ppm) | 200 ppm |
| ACGIH | ACGIH STEL (mg/m³) | 1040 mg/m³ |

PRO-WASH™ D Detergent Removable Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

| propyl acetate (109-60-4) | | |
|--|------------------------|---------------|
| ACGIH | ACGIH STEL (ppm) | 250 ppm |
| ACGIH | Remark (ACGIH) | Eye & URT irr |
| OSHA | OSHA PEL (TWA) (mg/m³) | 840 mg/m³ |
| OSHA | OSHA PEL (TWA) (ppm) | 200 ppm |
| Canada (Quebec) | VECD (mg/m³) | 1040 mg/m³ |
| Canada (Quebec) | VECD (ppm) | 250 ppm |
| Canada (Quebec) | VEMP (mg/m³) | 835 mg/m³ |
| Canada (Quebec) | VEMP (ppm) | 200 ppm |
| Docusate sodium USP (577-11-7) | | |
| ACGIH | Not applicable | |
| OSHA | Not applicable | |
| 4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (2786-76-7) | | |
| ACGIH | Not applicable | |
| OSHA | Not applicable | |
| C.I. Solvent Black 29 (117527-94-3) | | |
| ACGIH | Not applicable | |
| OSHA | Not applicable | |

8.2. Exposure controls

| | |
|----------------------------------|---|
| Appropriate engineering controls | : Avoid creating mist or spray. Ensure good ventilation of the work station. |
| Personal protective equipment | : Avoid all unnecessary exposure. |
| Hand protection | : None under normal use. In case of repeated or prolonged contact wear gloves. Use rubber gloves. |
| Eye protection | : None under normal use. In case of splashing or aerosol production: protective goggles. |
| Respiratory protection | : None under normal use. In case of inadequate ventilation wear respiratory protection. Use an approved respirator equipped with oil/mist cartridges. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| Physical state | : Liquid |
| Appearance | : Solid marker containing liquid colored paint. |
| Colour | : Variable. |
| Odour | : No data available |
| Odour threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butyl acetate=1) | : 1.7 |
| Melting point | : No data available |
| Freezing point | : -88.88 °C |
| Boiling point | : 82.5 °C |
| Flash point | : 12 °C |
| Auto-ignition temperature | : 399 °C |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapour pressure | : 4 kPa (30 mm Hg) @ 20 °C |
| Relative vapour density at 20 °C | : No data available |
| Relative density | : No data available |
| Solubility | : No data available |
| Log Pow | : No data available |
| Log Kow | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |

PRO-WASH™ D Detergent Removable Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Explosive limits : No data available

9.2. Other information

VOC content : 64.59 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Highly flammable liquid and vapour.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Open flame. Direct sunlight. Heat.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May release flammable gases. Thermal decomposition generates : Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| ethanol (64-17-5) | |
|--|------------------------------|
| LD50 oral rat | 10470 mg/kg |
| LD50 dermal rabbit | > 20000 mg/kg |
| LC50 inhalation rat (mg/l) | 133.8 mg/l/4h |
| ATE CLP (oral) | 10470.000 mg/kg bodyweight |
| ATE CLP (vapours) | 133.800 mg/l/4h |
| ATE CLP (dust,mist) | 133.800 mg/l/4h |
| Isopropanol (67-63-0) | |
| LD50 oral rat | 5840 mg/kg |
| LD50 dermal rabbit | 16.4 ml/kg |
| LC50 inhalation rat (ppm) | > 10000 ppm/4h |
| ATE CLP (oral) | 5840.000 mg/kg bodyweight |
| propyl acetate (109-60-4) | |
| LD50 oral rat | 8700 mg/kg |
| LD50 dermal rabbit | > 17800 mg/kg |
| LC50 inhalation rat (mg/l) | 32 mg/l/4h |
| ATE CLP (oral) | 8700.000 mg/kg bodyweight |
| ATE CLP (vapours) | 32.000 mg/l/4h |
| ATE CLP (dust,mist) | 32.000 mg/l/4h |
| 4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (2786-76-7) | |
| LD50 oral rat | > 15000 mg/kg |
| LC50 inhalation rat (mg/l) | > 1580 mg/m ³ 4 h |
| C.I. Solvent Black 29 (117527-94-3) | |
| LD50 oral rat | > 5000 mg/kg bodyweight |
| LD50 dermal rat | > 2000 mg/kg bodyweight |

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified.

Respiratory or skin sensitisation : Not classified.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified.

| Isopropanol (67-63-0) | |
|-----------------------|----------------------|
| IARC group | 3 - Not classifiable |

Reproductive toxicity : Not classified

PRO-WASH™ D Detergent Removable Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms

Symptoms/injuries after skin contact : May cause moderate irritation.

Symptoms/injuries after eye contact : Direct contact with the eyes is likely to be irritating.

Likely routes of exposure : Inhalation;Skin and eye contact

SECTION 12: Ecological information

12.1 Toxicity

| ethanol (64-17-5) | |
|--|-----------------|
| LC50 fish 1 | 14200 mg/l |
| EC50 Daphnia 1 | 5012 mg/l |
| Isopropanol (67-63-0) | |
| LC50 fish 1 | 10000 mg/l |
| propyl acetate (109-60-4) | |
| LC50 fish 1 | 60 mg/l 96 h |
| EC50 Daphnia 1 | 91.5 mg/l 48 h |
| 4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (2786-76-7) | |
| LC50 fish 1 | > 500 mg/l 96 h |
| EC50 Daphnia 1 | > 110 mg/l 48 h |
| C.I. Solvent Black 29 (117527-94-3) | |
| LC50 fish 1 | 2 mg/l 96 h |

12.2. Persistence and degradability

| ethanol (64-17-5) | |
|--|----------------------------|
| Biodegradation | > 96 % 28 d |
| Isopropanol (67-63-0) | |
| Persistence and degradability | Readily biodegradable. |
| propyl acetate (109-60-4) | |
| Persistence and degradability | Readily biodegradable. |
| Biodegradation | 62 % 5 d |
| 4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (2786-76-7) | |
| Persistence and degradability | Not readily biodegradable. |
| Biodegradation | 0 % 28 d |
| C.I. Solvent Black 29 (117527-94-3) | |
| Persistence and degradability | Not readily biodegradable. |

12.3. Bioaccumulative potential

| ethanol (64-17-5) | |
|--|--------------------------------|
| Bioaccumulative potential | Not expected to bioaccumulate. |
| Isopropanol (67-63-0) | |
| Bioaccumulative potential | Not expected to bioaccumulate. |
| propyl acetate (109-60-4) | |
| Log Pow | 1.23 |
| 4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (2786-76-7) | |
| BCF fish 1 | 53 l/kg |
| Log Pow | 1.28 |
| C.I. Solvent Black 29 (117527-94-3) | |
| Log Pow | < 3.7 @ 20 °C |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

PRO-WASH™ D Detergent Removable Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

| | |
|---------------------------------|---|
| Sewage disposal recommendations | : Do not dispose of waste into sewer. |
| Waste disposal recommendations | : Dispose in a safe manner in accordance with local/national regulations. |
| Additional information | : Handle empty containers with care because residual vapours are flammable. |
| Ecology - waste materials | : Avoid release to the environment. |

SECTION 14: Transport information

In accordance with DOT and TDG

| | |
|----------------------------------|---|
| Transport document description | : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, II |
| UN-No.(DOT) | : UN1263 |
| Proper Shipping Name (DOT) | : Paint including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base |
| Transport hazard class(es) (DOT) | : 3 - Flammable liquid |
| Packing group (DOT) | : II - Medium Danger |

ADR

| | |
|--------------------------------|-------------------------------|
| Transport document description | : UN 1263 PAINT, 3, II, (D/E) |
| Proper Shipping Name (ADR) | : PAINT |
| Packing group (ADR) | : II |
| Class (ADR) | : 3 - Flammable liquid |

Transport by sea

| | |
|-----------------------------|-------------------------|
| UN-No. (IMDG) | : UN 1263 |
| Proper Shipping Name (IMDG) | : PAINT |
| Class (IMDG) | : 3 - Flammable liquids |
| Packing group (IMDG) | : II |

Air transport

| | |
|-----------------------------|-------------------------|
| UN-No.(IATA) | : UN 1263 |
| Proper Shipping Name (IATA) | : Paint |
| Class (IATA) | : 3 - Flammable Liquids |
| Packing group (IATA) | : II |

SECTION 15: Regulatory information

15.1. US Federal regulations

ethanol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Isopropanol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

| | |
|-------------------------------------|-------------|
| SARA Section 311/312 Hazard Classes | Fire hazard |
|-------------------------------------|-------------|

propyl acetate (109-60-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (2786-76-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

C.I. Solvent Black 29 (117527-94-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Isopropanol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

PRO-WASH™ D Detergent Removable Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

propyl acetate (109-60-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (2786-76-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

C.I. Solvent Black 29 (117527-94-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

ethanol (64-17-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Isopropanol (67-63-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

propyl acetate (109-60-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

4-[[4-(aminocarbonyl)phenyl]azo]-N-(2-ethoxyphenyl)-3-hydroxynaphthalene-2-carboxamide, C.I. Pigment Red 170 (2786-76-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances)

C.I. Solvent Black 29 (117527-94-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

PRO-WASH™ D Detergent Removable Paint Markers

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).

All ingredients are listed in the Toxic Substances Control Act (TSCA).

All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

15.3. US State regulations

ethanol (64-17-5)

U.S. - New Jersey - Right to Know Hazardous Substance List

Isopropanol (67-63-0)

U.S. - Minnesota - Hazardous Substance List

U.S. - New Jersey - Right to Know Hazardous Substance List

propyl acetate (109-60-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

Indication of changes

: Revised format.

Data sources

: ACGIH (American Conference of Government Industrial Hygienists).

European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.

Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.

National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.

OSHA 29CFR 1910.1200 Hazard Communication Standard.

TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Abbreviations and acronyms

: ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number.

CLP: Classification, Labelling, Packaging.

EC50: Environmental Concentration associated with a response by 50% of the test population.

GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).

LD50: Lethal Dose for 50% of the test population.

OSHA: Occupational Safety & Health Administration.

PBT: Persistent, Bioaccumulative, Toxic.

TWA: Time Weight Average.

TSCA: Toxic Substances Control Act.

Other information


: None.

PRO-WASH™ D Detergent Removable Paint Markers

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

| | |
|--------------------|--|
| NFPA health hazard | : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given. |
| NFPA fire hazard | : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur. |
| NFPA reactivity | : 0 - Normally stable, even under fire exposure conditions, and not reactive with water. |



Full text of H-phrases:

| | |
|-------------------|--|
| Aquatic Chronic 2 | Hazardous to the aquatic environment — Chronic Hazard, Category 2 |
| Eye Irrit. 2A | Serious eye damage/eye irritation, Category 2A |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| Skin Sens. 1 | Sensitisation — Skin, category 1 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| H225 | Highly flammable liquid and vapour |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H319 | Causes serious eye irritation |
| H336 | May cause drowsiness or dizziness |
| H411 | Toxic to aquatic life with long lasting effects |

SDS Prepared by: The Redstone Group, LLC
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43016
T 614-923-7472
www.redstonegrp.com

LACO NA GHS SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product