

NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Safety Data Sheet P-18-20666

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/31/2017

SECTION: 1. Product and company identification

1.1. Product identifier

Product form : Mixture
 Product name : NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%
 Other means of identification : Mixture of 1-Butene, 2-methyl-1-Butene, Butane, Isobutane, Isobutylene, Isopentane, trans-2-Butene and Nitrogen

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use. Use as directed.

1.3. Details of the supplier of the safety data sheet

Praxair, Inc.
 10 Riverview Drive
 Danbury, CT 06810-6268 - USA
 T 1-800-772-9247 (1-800-PRAXAIR) - F 1-716-879-2146
www.praxair.com

1.4. Emergency telephone number

Emergency number : Onsite Emergency: 1-800-645-4633

CHEMTREC, 24 hr/day 7 days/week
 — Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887
 (collect calls accepted, Contract 17729)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Gas 1 H220
 Compressed gas H280
 Aquatic Acute 3 H402

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS04

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H220 - **EXTREMELY FLAMMABLE GAS**
 H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED
 H402 - HARMFUL TO AQUATIC LIFE
 CGA-HG04 - MAY FORM EXPLOSIVE MIXTURES WITH AIR
 OSHA-H01 - MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.

Precautionary statements (GHS-US) :

P210 - Keep away from Heat/Open flames/Sparks/Hot surfaces. - No smoking
 P273 - Avoid release to the environment.
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
 P381 - Eliminate all ignition sources if safe to do so.



NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Safety Data Sheet P-18-20666

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/31/2017

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).
P501 - Dispose of contents/container in accordance with container Supplier/owner instructions.
P271+P403 - Use and store only outdoors or in a well-ventilated place.

2.3. Other hazards

Other hazards not contributing to the classification : Asphyxiant in high concentrations.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Nitrogen	(CAS No) 7727-37-9	72 - 95
2-Methyl-1-butene	(CAS No) 563-46-2	0.5 - 4
Isopentane	(CAS No) 78-78-4	0.5 - 4
trans-2-Butene	(CAS No) 624-64-6	0.5 - 4
1-Butene	(CAS No) 106-98-9	0.5 - 4
Isobutylene	(CAS No) 115-11-7	1 - 4
Isobutane	(CAS No) 75-28-5	1 - 4
Butane	(CAS No) 106-97-8	1 - 4

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Call a physician.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately..

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide, Dry chemical, Water spray or fog. Use extinguishing media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : **EXTREMELY FLAMMABLE GAS.**

Explosion hazard : **EXTREMELY FLAMMABLE GAS.** Forms explosive mixtures with air and oxidizing agents.

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Safety Data Sheet P-18-20666

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/31/2017

5.3. Advice for firefighters

Firefighting instructions	: Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards (e.g. 29 CFR 1910 Subpart L—Fire Protection in the U.S.).
Protection during firefighting	: Compressed gas: asphyxiant. Suffocation hazard by lack of oxygen. Danger! FLAMMABLE, HIGH PRESSURE GAS.
Special protective equipment for fire fighters	: Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
Other information	: Containers are equipped with a pressure relief device. (Exceptions may exist where authorized.)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: If venting or leaking gas catches fire, do not extinguish flames. Flammable vapors may spread from leak, creating an explosive reignition hazard. Vapors can be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge, or other ignition sources at locations distant from product handling point. Explosive atmospheres may linger. Before entering an area, especially a confined area, check the atmosphere with an appropriate device.
------------------	--

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Use only explosion-proof equipment. Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g. wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.
-------------------------------	---



NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Safety Data Sheet P-18-20666

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/31/2017

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store only where temperature will not exceed 125°F (52°C). Post "No Smoking/No Open Flames" signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g., NFPA 30, NFPA 55, NFPA 70, and/or NFPA 221 in the U.S.) or according to requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16.

Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-Methyl-1-butene (563-46-2)		
Isopentane (78-78-4)		
ACGIH	ACGIH TLV-TWA (ppm)	1000 ppm
USA OSHA	Not established	
trans-2-Butene (624-64-6)		
ACGIH	ACGIH TLV-TWA (ppm)	250 ppm
1-Butene (106-98-9)		
ACGIH	ACGIH TLV-TWA (ppm)	250 ppm
USA OSHA	Not established	
Isobutylene (115-11-7)		
ACGIH	ACGIH TLV-TWA (ppm)	250 ppm
Isobutane (75-28-5)		
ACGIH	ACGIH TLV-TWA (ppm)	1000 ppm
ACGIH	ACGIH TLV-STEL (ppm)	1000 ppm
USA OSHA	Not established	
Butane (106-97-8)		
ACGIH	ACGIH TLV-STEL (ppm)	1000 ppm
USA OSHA	Not established	

NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Safety Data Sheet P-18-20666

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/31/2017

Nitrogen (7727-37-9)	
ACGIH	Not established
USA OSHA	Not established

8.2. Exposure controls

- Appropriate engineering controls : Use an explosion-proof local exhaust system. Local exhaust and general ventilation must be adequate to meet exposure standards. MECHANICAL (GENERAL): **Inadequate - Use only in a closed system.** Use explosion proof equipment and lighting. Provide adequate general and local exhaust ventilation. Ensure exposure is below occupational exposure limits (where available).
- Eye protection : Wear safety glasses with side shields.
- Skin and body protection : Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where needed. Wear appropriate chemical gloves during cylinder changeout or wherever contact with product is possible.
- Respiratory protection : When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).
- Thermal hazard protection : Wear cold insulating gloves when transfilling or breaking transfer connections.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Gas
- Colour : Colourless
- Odour : No data available
- Odour threshold : No data available
- pH : Not applicable.
- Relative evaporation rate (butylacetate=1) : No data available
- Relative evaporation rate (ether=1) : Not applicable.
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : No data available
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : No data available
- Vapour pressure : Not applicable.
- Relative vapour density at 20 °C : No data available
- Relative density : No data available
- Solubility : Water: No data available
- Log Pow : Not applicable.
- Log Kow : Not applicable.
- Viscosity, kinematic : Not applicable.
- Viscosity, dynamic : Not applicable.
- Explosive properties : Not applicable.



NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Safety Data Sheet P-18-20666

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/31/2017

Oxidizing properties : None.
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Isobutylene (115-11-7)	
LC50 inhalation rat (ppm)	541657 ppm/1h
ATE US (gases)	270828.500 ppmv/4h
Isobutane (75-28-5)	
LC50 inhalation rat (ppm)	285000 ppm/1h
ATE US (gases)	142500.000 ppmv/4h
ATE US (vapours)	658.000 mg/l/4h
ATE US (dust,mist)	658.000 mg/l/4h

Skin corrosion/irritation : Not classified
pH: Not applicable.

Serious eye damage/irritation : Not classified
pH: Not applicable.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Isobutylene (115-11-7)	
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Safety Data Sheet P-18-20666

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/31/2017

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Isopentane (78-78-4)	
EC50 Daphnia 1	2.3 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Persistence and degradability : No ecological damage caused by this product.

Isopentane (78-78-4)
Persistence and degradability : Not established.

trans-2-Butene (624-64-6)
Persistence and degradability : No data available.

1-Butene (106-98-9)
Persistence and degradability : Not readily biodegradable.

Isobutylene (115-11-7)
Persistence and degradability : The substance is biodegradable. Unlikely to persist.

Isobutane (75-28-5)
Persistence and degradability : The substance is biodegradable. Unlikely to persist.

Butane (106-97-8)
Persistence and degradability : The substance is biodegradable. Unlikely to persist.

Nitrogen (7727-37-9)
Persistence and degradability : No ecological damage caused by this product.

12.3. Bioaccumulative potential

NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Log Pow : Not applicable.

Log Kow : Not applicable.

Bioaccumulative potential : No ecological damage caused by this product.

Isopentane (78-78-4)
Log Pow : 3.2 - 3.3
Bioaccumulative potential : Not established.

trans-2-Butene (624-64-6)
Log Pow : 2.32
Bioaccumulative potential : Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

1-Butene (106-98-9)
Log Pow : 2.4
Bioaccumulative potential : Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

Isobutylene (115-11-7)
Log Pow : 2.35
Bioaccumulative potential : Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Safety Data Sheet P-18-20666

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/31/2017

Isobutane (75-28-5)	
BCF fish 1	1.57 - 1.97
Log Pow	2.76
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

Butane (106-97-8)	
Log Pow	2.89
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

Nitrogen (7727-37-9)	
Log Pow	Not applicable for inorganic gases.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

12.4. Mobility in soil

NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%	
Mobility in soil	No data available.

trans-2-Butene (624-64-6)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

1-Butene (106-98-9)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

Isobutylene (115-11-7)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

Isobutane (75-28-5)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

Butane (106-97-8)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

Nitrogen (7727-37-9)	
Mobility in soil	No data available.
Ecology - soil	No ecological damage caused by this product.

12.5. Other adverse effects

Effect on the ozone layer : None.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

SECTION 14: Transport information

In accordance with DOT
 Transport document description : UN1954 Compressed gas, flammable, n.o.s., 2.1
 UN-No.(DOT) : UN1954
 Proper Shipping Name (DOT) : Compressed gas, flammable, n.o.s.

NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Safety Data Sheet P-18-20666

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/31/2017

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Symbols : G - Identifies proper shipping name (PSN) requiring the addition of technical name(s) in parentheses following the PSN.

Additional information

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:
- Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transport by sea

UN-No. (IMDG) : 1954
Proper Shipping Name (IMDG) : COMPRESSED GAS, FLAMMABLE, N.O.S.
Class (IMDG) : 2.1 - Flammable gases

Air transport

UN-No. (IATA) : 1954
Proper Shipping Name (IATA) : COMPRESSED GAS, FLAMMABLE, N.O.S.
Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

Isopentane (78-78-4)

Listed on the Canadian DSL (Domestic Substances List)

Isobutane (75-28-5)

Listed on the Canadian DSL (Domestic Substances List)

Butane (106-97-8)

Listed on the Canadian DSL (Domestic Substances List)

Nitrogen (7727-37-9)

Listed on the Canadian DSL (Domestic Substances List)

NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Safety Data Sheet P-18-20666

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/31/2017

EU-Regulations

15.2.2. National regulations

No additional information available

15.3. US State regulations

NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%()	
U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

2-Methyl-1-butene (563-46-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Isopentane (78-78-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

trans-2-Butene (624-64-6)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

1-Butene (106-98-9)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Isobutylene (115-11-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Isobutane (75-28-5)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	



NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Safety Data Sheet P-18-20666

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/31/2017

Isobutane (75-28-5)				
		Female		
No	No	No	No	

Butane (106-97-8)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Nitrogen (7727-37-9)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

2-Methyl-1-butene (563-46-2)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Isopentane (78-78-4)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

trans-2-Butene (624-64-6)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

1-Butene (106-98-9)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Isobutylene (115-11-7)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Isobutane (75-28-5)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Butane (106-97-8)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List				

Nitrogen (7727-37-9)				
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List				



NI - 1-Butene 0.5%-4%, 2-methyl-1-Butene 0.5%-4%, Butane 1%-4%, Isobutane 1%-4%, Isobutylene 1%-4%, Isopentane 0.5%-4%, trans-2-Butene 0.5%-4%

Safety Data Sheet P-18-20666

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/31/2017

Nitrogen (7727-37-9)

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair, Inc, it is the user's obligation to determine the conditions of safe use of the product.

Praxair SDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from www.praxair.com. If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (Phone: 1-800-PRAXAIR/1-800-772-9247; Address: Praxair Call Center, Praxair, Inc, P.O. Box 44, Tonawanda, NY 14151-0044).

PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

SDS US (GHS HazCom 2012) - PDI

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.