

SECTION 1: Product and company identification

1.1. Product identifier

Product form : Mixture
Other means of identification : Mixture of oxygen 14.46% to 99.99% in argon.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use. Use as directed.

1.3. Details of the supplier of the safety data sheet

Praxair, Inc.
39 Old Ridgebury Road
Danbury, CT 06810-5113 - USA
T 1-800-772-9247 (1-800-PRAXAIR) - F 1-716-879-2146
www.praxair.com

1.4. Emergency telephone number

Emergency number : Onsite Emergency: 1-800-645-4633

CHEMTREC, 24 hr/day 7 days/week — Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887 (collect calls accepted, Contract 17729)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Ox. Gas 1 H270
Compressed gas H280

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS03

GHS04

Signal word (GHS-US) :

DANGER

Hazard statements (GHS-US) :

H270 - MAY CAUSE OR INTENSIFY FIRE; OXIDIZER
H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

Precautionary statements (GHS-US) :

P220 - Keep/Store away from clothing, combustibles
P244 - Keep reduction valves/valves and fittings free from oil and grease
P370+P376 - In case of fire: stop leak if safe to do so
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).
P271+P403 - Use and store only outdoors or in a well-ventilated place.
CGA-PG20+CGA-PG22+CGA-PG32 - Use only with compatible materials of construction, with equipment cleaned for oxygen service, and with equipment passivated before use.
CGA-PG21 - Open valve slowly.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Oxygen	(CAS No) 7782-44-7	14.46 - 99.99
Argon	(CAS No) 7440-37-1	0.01 - 85.54

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Immediately remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.
- First-aid measures after skin contact : Adverse effects not expected from this product.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately.
- First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

- Reactivity : No reactivity hazard other than the effects described in sub-sections below.

5.3. Advice for firefighters

- Firefighting instructions : Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.
- Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
- Other information : Containers are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Try to stop release. Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Argon (7440-37-1)	
ACGIH	Not established
USA OSHA	Not established
Oxygen (7782-44-7)	
ACGIH	Not established
USA OSHA	Not established

8.2. Exposure controls

Appropriate engineering controls : Systems under pressure should be regularly checked for leakages. Ensure exposure is below occupational exposure limits (where available). Gas detectors should be used when oxidising gases may be released. Provide adequate general and local exhaust ventilation.

Eye protection : Wear safety glasses when handling cylinders; vapor-proof goggles and a face shield during cylinder changeout or whenever contact with product is possible. Select eye protection in accordance with OSHA 29 CFR 1910.133.

Skin and body protection : Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where needed. Wear appropriate chemical gloves during cylinder changeout or wherever contact with product is possible. Select per OSHA 29 CFR 1910.132, 1910.136, and 1910.138.

Respiratory protection	: When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure (e.g., an organic vapor cartridge). For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).
	Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.
Thermal hazard protection	: Wear cold insulating gloves when transfilling or breaking transfer connections.
Other information	: Consider the use of flame resistant safety clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Colour	: Colourless
Odour	: No data available
Odour threshold	: No data available
pH	: Not applicable.
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable.
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: Not applicable.
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Water: No data available
Log Pow	: Not applicable.
Log Kow	: Not applicable.
Viscosity, kinematic	: Not applicable.
Viscosity, dynamic	: Not applicable.
Explosive properties	: Not applicable.
Oxidising properties	: Oxidiser.
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Violently oxidises organic material.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

May react violently with combustible materials. May react violently with reducing agents.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified pH: Not applicable.
Serious eye damage/irritation	: Not classified pH: Not applicable.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

AR - Oxygen 14.46% - 99.99%	
Persistence and degradability	No ecological damage caused by this product.
Argon (7440-37-1)	
Persistence and degradability	No ecological damage caused by this product.
Oxygen (7782-44-7)	
Persistence and degradability	No ecological damage caused by this product.

12.3. Bioaccumulative potential

AR - Oxygen 14.46% - 99.99%	
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.
Argon (7440-37-1)	
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.
Oxygen (7782-44-7)	
Log Pow	Not applicable.
Log Kow	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

12.4. Mobility in soil

AR - Oxygen 14.46% - 99.99%	
Mobility in soil	No data available.
Argon (7440-37-1)	
Mobility in soil	No data available.
Ecology - soil	No ecological damage caused by this product.
Oxygen (7782-44-7)	
Mobility in soil	No data available.
Ecology - soil	No ecological damage caused by this product.

12.5. Other adverse effects

Effect on ozone layer : None.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not discharge into any place where its accumulation could be dangerous. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods. Ensure that the emission levels from local regulations or operating permits are not exceeded. Do not attempt to dispose of residual or unused quantities. Return container to supplier.

Waste disposal recommendations : Do not attempt to dispose of residual or unused quantities. Return container to supplier.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN3156 Compressed gas, oxidizing, n.o.s.

UN-No.(DOT) : UN3156

Proper Shipping Name (DOT) : Compressed gas, oxidizing, n.o.s.

Hazard labels (DOT) : 2.2 - Non-flammable gas
 5.1 - Oxidiser



DOT Symbols : G - Identifies proper shipping name (PSN) requiring the addition of technical name(s) in parentheses following the PSN.

DOT Special Provisions (49 CFR 172.102) : A14 - This material is not authorized to be transported as a limited quantity or consumer commodity in accordance with 173.306 of this subchapter when transported aboard an aircraft.

Additional information

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:
 - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transport by sea

UN-No. (IMDG) : 3156

Proper Shipping Name (IMDG) : COMPRESSED GAS, OXIDIZING, N.O.S.

Class (IMDG) : 2.2 - Non-flammable, non-toxic gases

Air transport

UN-No.(IATA) : 3156



AR - Oxygen 14.46% - 99.99%

Safety Data Sheet P-18-2071

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 05/22/2015

Proper Shipping Name (IATA) : COMPRESSED GAS, OXIDIZING, N.O.S.
 Class (IATA) : 2

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

Argon (7440-37-1)

Listed on the Canadian DSL (Domestic Substances List)

Oxygen (7782-44-7)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

15.2.2. National regulations

No additional information available

15.3. US State regulations

AR - Oxygen 14.46% - 99.99%(I)

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

Argon (7440-37-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	

Oxygen (7782-44-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	

Argon (7440-37-1)

U.S. - Massachusetts - Right To Know List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

Oxygen (7782-44-7)

U.S. - Massachusetts - Right To Know List
 U.S. - New Jersey - Right to Know Hazardous Substance List
 U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair SDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from www.praxair.com. If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (Phone: 1-800-PRAXAIR/1-800-772-9247; Address: Praxair Call Center, Praxair, Inc., P.O. Box 44, Tonawanda, NY 14151-0044).

PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

SDS US (GHS HazCom 2012) - PDI

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.