

Safety Data Sheet P-4618

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Date of issue: 01/01/1978 Revision date: 03/09/2015 Supersedes: 03/04/2015

SECTION: 1. Product and company identification

Product identifier

Product form : Substance

Name : Methane, compressed

CAS No 74-82-8 Formula CH4

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use. Use as directed.

1.3. Details of the supplier of the safety data sheet

Praxair, Inc.

39 Old Ridgebury Road

Danbury, CT 06810-5113 - USA

T 1-800-772-9247 (1-800-PRAXAIR) - F 1-716-879-2146

www.praxair.com

Emergency telephone number

Emergency number : Onsite Emergency: 1-800-645-4633

CHEMTREC, 24hr/day 7days/week — Within USA: 1-800-424-9300, Outside USA: 001-703-

527-3887 (collect calls accepted, Contract 17729)

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification (GHS-US)

Flam, Gas 1 H220 Compressed gas H280

Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS04

Signal word (GHS-US) : DANGER

Hazard statements (GHS-US) H220 - EXTREMELY FLAMMABLE GAS

H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED OSHA-H01 - MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.

CGA-HG04 - MAY FORM EXPLOSIVE MIXTURES WITH AIR

Precautionary statements (GHS-US) : P202 - Do not handle until all safety precautions have been read and understood

P210 - Keep away from Heat, Open flames, Sparks, Hot surfaces. - No smoking

P271+P403 - Use and store only outdoors or in a well-ventilated place.

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely

P381 - Eliminate all ignition sources if safe to do so

CGA-PG05 - Use a back flow preventive device in the piping. CGA-PG10 - Use only with equipment rated for cylinder pressure.

CGA-PG06 - Close valve after each use and when empty.

CGA-PG11 - Never put cylinders into unventilated areas of passenger vehicles. CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

Other hazards

Other hazards not contributing to the : None.

EN (English US) SDS ID: P-4618 1/9

This document is only controlled while on the Praxair, Inc. website and a copy of this controlled version is available for download. Praxair cannot assure the integrity or accuracy of any version of this document after it has been downloaded or removed from our website.



Safety Data Sheet P-4618

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1978 Revision date: 03/09/2015 Supersedes: 03/04/2015

classification

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Name : Methane, compressed

CAS No : 74-82-8

Name	Product identifier	%
Methane	(CAS No) 74-82-8	100

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Immediately remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, qualified personnel may give oxygen. Call a physician.

First-aid measures after skin contact : If skin irritation occurs: Wash with plenty of soap and water.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and

away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an

ophthalmologist immediately.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide, Dry chemical, Water spray or fog.

5.2. Special hazards arising from the substance or mixture

Fire hazard : EXTREMELY FLAMMABLE GAS. If venting or leaking gas catches fire, do not extinguish

flames. Flammable vapors may spread from leak, creating an explosive reignition hazard. Vapors can be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge, or other ignition sources at locations distant from product handling point. Explosive atmospheres may linger. Before entering an area, especially a confined area,

check the atmosphere with an appropriate device.

Explosion hazard : EXTREMELY FLAMMABLE GAS. Forms explosive mixtures with air and oxidizing agents.

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

5.3. Advice for firefighters

Firefighting instructions : DANGER! Flammable, high pressure gas.

Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart

L—Fire Protection.

Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters.

Other information : Containers are equipped with a pressure relief device. (Exceptions may exist where authorized

by DOT.).

EN (English US) SDS ID: P-4618 2/9



Safety Data Sheet P-4618

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1978 Revision date: 03/09/2015 Supersedes: 03/04/2015

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: DANGER: EXTREMELY FLAMMABLE GAS. Forms explosive mixtures with air and oxidizing agents. See section 5. Evacuate personnel to a safe area. Appropriate self-contained breathing apparatus may be required. Approach suspected leak area with caution. Remove all sources of ignition. if safe to do so. Reduce gas with fog or fine water spray. Stop flow of product if safe to do so. Ventilate area or move container to a well-ventilated area. Flammable gas may spread from leak. Before entering the area, especially a confined area, check the atmosphere with an appropriate device.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Use only explosion-proof equipment.

Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store only where temperature will not exceed 125°F (52°C). Post "No Smoking or Open Flames" signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g., NFPA 30, NFPA 55, NFPA 70, and/or NFPA 221 in the U.S.) or according to requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

EN (English US) SDS ID: P-4618 3/9



Safety Data Sheet P-4618

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1978 Revision date: 03/09/2015 Supersedes: 03/04/2015

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methane, compressed (74-82-8)		
ACGIH	Not established	
USA OSHA	Not established	
Methane (74-82-8)		
Methane (74-82-8)		
Methane (74-82-8) ACGIH	Not established	

8.2. Exposure controls

Appropriate engineering controls : Use an explosion-proof local exhaust system with sufficient flow velocity to maintain an

adequate supply of air in the worker's breathing zone. Mechanical/General measures: Use in

a closed system.

Eye protection : Wear safety glasses when handling cylinders; vapor-proof goggles and a face shield during

cylinder changeout or whenever contact with product is possible. Select eye protection in

accordance with OSHA 29 CFR 1910.133.

Skin and body protection : Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where

needed. Wear neoprene gloves during cylinder changeout or wherever contact with product is

possible. Select per OSHA 29 CFR 1910.132, 1910.136, and 1910.138.

Respiratory protection : When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable).

Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the

Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure (e.g., an organic vapor cartridge). For emergencies or instances with unknown exposure levels, use a

self-contained breathing apparatus (SCBA).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Colorless gas.

Molecular mass : 16.04 g/mol
Color : Colorless

Odor : No data available
Odor threshold : No data available
pH : Not applicable.
Relative evaporation rate (butyl acetate=1) : Not applicable
Relative evaporation rate (ether=1) : Not applicable.

Melting point : -182 °C

Freezing point : No data available
Boiling point : -161.5 °C
Flash point : -187.8 °C
Critical temperature : -82.5
Auto-ignition temperature : 600 °C

Decomposition temperature : No data available Flammability (solid, gas) : 5 - 15 vol % Vapor pressure : Not applicable. Critical pressure : 4599 kPa Relative vapor density at 20 °C : No data available

EN (English US) SDS ID: P-4618 4/9



Safety Data Sheet P-4618

Making our planet more productive according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1978 Revision date: 03/09/2015 Supersedes: 03/04/2015

Relative density : 0.56

Specific gravity / density : 0.66 kg/m³ Vapor density @15.6°C, 1 atm

Relative gas density : 0.7 @15.6°C, 1 atm Solubility : Water: No data available

Log Pow: Not applicable.Log Kow: Not applicable.Viscosity, kinematic: Not applicable.Viscosity, dynamic: Not applicable.Explosive properties: Not applicable.

Oxidizing properties : None.

Explosive limits : No data available

9.2. Other information

Gas group : Compressed gas

Additional information : None.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

May occur.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

10.5. Incompatible materials

Oxidizing agents. May explode: Bromine pentafluoride. Chlorine. Mercury oxide. Nitrogen trifluoride.

Liquid Oxygen. Oxygen difluoride.

10.6. Hazardous decomposition products

Thermal decomposition may produce: Carbon dioxide. Carbon monoxide. Hydrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Skin corrosion/irritation : Not classified

pH: Not applicable.

Serious eye damage/irritation : Not classified

pH: Not applicable.

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard

: Not classified

EN (English US) SDS ID: P-4618 5/9



Safety Data Sheet P-4618

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1978 Revision date: 03/09/2015 Supersedes: 03/04/2015

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No known ecological damage caused by this product.

12.2. Persistence and degradability

Methane, compressed (74-82-8)		
Persistence and degradability	The substance is biodegradable. Unlikely to persist.	
Methane (74-82-8)		
Persistence and degradability	The substance is biodegradable. Unlikely to persist.	

12.3. Bioaccumulative potential

Methane, compressed (74-82-8)		
Log Pow	Not applicable.	
Log Kow	Not applicable.	
Bioaccumulative potential No ecological damage caused by this product.		
Methane (74-82-8)		
Log Pow	1.09	
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.	

12.4. Mobility in soil

Methane, compressed (74-82-8)	
Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.
Methane (74-82-8)	
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Other adverse effects

Effect on ozone layer : None. Global warming potential [CO2=1] : 21

Effect on the global warming : When discharged in large quantities may contribute to the greenhouse effect.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Do not attempt to dispose of residual or unused quantities. Return container to supplier.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1971 Methane, compressed, 2.1

UN-No.(DOT) : UN1971

Proper Shipping Name (DOT) : Methane, compressed

Hazard Classes (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



Additional information

Emergency Response Guide (ERG) Number : 115 (UN1971)

Other information : No supplementary information available.

EN (English US) SDS ID: P-4618 6/9



Safety Data Sheet P-4618

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication. Date of issue: 01/01/1978 Revision date: 03/09/2015 Supersedes: 03/04/2015

Special transport precautions

: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transport by sea

UN-No. (IMDG) : 1971

Proper Shipping Name (IMDG) : METHANE, COMPRESSED

Class (IMDG) : 2 - Gases MFAG-No : 115

Air transport

UN-No.(IATA) : 1971

Proper Shipping Name (IATA) : Methane, compressed

Class (IATA)

Civil Aeronautics Law : Gases under pressure/Gases flammable under pressure

SECTION 15: Regulatory information

15.1. US Federal regulations

Methane, compressed (74-82-8)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
SARA Section 311/312 Hazard Classes Sudden release of pressure hazard Fire hazard		

All components of this product are listed on the Toxic Substances Control Act

(TSCA) inventory.

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Methane, compressed (74-82-8)

Listed on the Canadian DSL (Domestic Substances List)

Methane (74-82-8)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Methane, compressed (74-82-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Methane, compressed (74-82-8)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

EN (English US) SDS ID: P-4618 7/9



Safety Data Sheet P-4618

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1978 Revision date: 03/09/2015 Supersedes: 03/04/2015

15.3. US State regulations	
Methane, compressed(74-82-8)	
U.S California - Proposition 65 - Carcinogens List	No No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S Massachusetts - Right To Know List U.S New Jersey - Right to Know Hazardous Substance List U.S Pennsylvania - RTK (Right to Know) List

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

Methane (74-82-8)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	

Methane (74-82-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Revision date

Other information

: 3/9/2015 12:00:00 AM

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Praxair asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Praxair, Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Praxair, Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair SDSs are furnished on sale or delivery by Praxair or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your Praxair sales representative, local distributor, or supplier, or download from www.praxair.com. If you have questions regarding Praxair SDSs, would like the document number and date of the latest SDS, or would like the names of the Praxair suppliers in your area, phone or write the Praxair Call Center (Phone: 1-800-PRAXAIR/1-800-772-9247; Address: Praxair Call Center, Praxair, Inc., P.O. Box 44, Tonawanda, NY 14151-0044).

PRAXAIR and the Flowing Airstream design are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries.

EN (English US) SDS ID: P-4618 8/9



Safety Data Sheet P-4618

according to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Date of issue: 01/01/1978 Revision date: 03/09/2015 Supersedes: 03/04/2015

NFPA health hazard : 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.


NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure

and temperature, or is readily dispersed in air and will burn

readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 0 Minimal Hazard - No significant risk to health

Flammability : 4 Severe Hazard Physical : 3 Serious Hazard

SDS US (GHS HazCom 2012) - Praxair

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.