

1. IDENTIFICATION

Product Identity / Trade Name: Sait Screen

Product Use: Restriction on Use:	Abrasive materials used for sanding metals, concrete, masonry and building materials. Use only as directed				
Manufacturer:	United Abrasives, Inc. 185 Boston Post Road North Windham, CT_06256				
Internet:	www.unitedabrasives.com				
Information Phone:	(860) 456-7131	Emergency Phone: (860) 456-7131			
Date of Preparation:	June 15, 2018				
2. HAZARD(S) IDENTIFICATION					

Classification: Not classified as hazardous as defined by the GHS and OSHA 29 CFR 1910.1200.

Label Elements: None Required.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Concentration
Backing (Cloth or Paper)	N/A	30-60
Silicon Carbide	409-21-2	10-30
Cured Resin	Mixture	5-30
Glue	Mixture	5-30

The specific identity and/or exact percentage has been withheld as a trade secret.

4. FIRST-AID MEASURES

Ingestion: If sanding dust is swallowed, seek medical attention.

Inhalation: If overexposed to sanding dust, remove victim to fresh air and get medical attention.

Eye Contact: Flush eyes thoroughly with water, holding open eyelids. Get medical attention if irritation persists. Obtain immediate medical attention for foreign body in the eye.

Skin Contact: Wash dust from skin with soap and water. Launder contaminated clothing before reuse.

Most important symptoms/effects, acute and delayed: Eye and skin contact with sanding dust may cause mechanical irritation.

Indication of immediate medical attention and special treatment, if necessary: Immediate medical attention is generally not required.

5. FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media: Use any media that is appropriate for the surrounding fire.

Specific hazards arising from the chemical: This product is not combustible, however, consideration must be given to the potential fire/explosion hazards from the base material being processed. Many materials create flammable/explosive dusts or turnings when sanded, machined or ground.

Special protective equipment and precautions for fire-fighters: Firefighters should wear full emergency equipment and NIOSH approved positive pressure self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Wear appropriate respirator and protective clothing as needed to avoid eye contact and inhalation of dust.

Environmental precautions: Avoid release into the environmental. Report releases as required by local, state and federal authorities.

Methods and materials for containment and cleaning up: Pick up, sweep up or vacuum and place in a container for disposal. Minimize generation of dust.

7. HANDLING AND STORAGE

Precautions for safe handling: Use only with adequate ventilation. Avoid breathing dust. Wash thoroughly after handling and use, especially before eating, drinking or smoking. Consider potential exposure to components of the base materials or coatings being ground. Refer to OSHA's substance specific standards for additional work practice requirements where applicable.

Conditions for safe storage, including any incompatibilities Store in a dry location.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines:

Backing (Cloth or Paper)	None Established
Silicon Carbide	3 mg/m3 TWA ACGIH TLV (respirable fraction) 10 mg/m3 TWA ACGIH TLV (inhalable fraction)
	15 mg/m3 TWA ACGIA TEV (initialable fraction) 5 mg/m3 TWA OSHA PEL (total dust)
Cured Resin	None Established
Glue	None Established

Note: Consider also components from base materials and coatings.

Appropriate engineering controls: Use local exhaust or general ventilation as required to minimize exposure to dust and maintain the concentration of contaminants below the exposure limits.

Individual protection measures, such as personal protective equipment:

Respiratory protection: Use NIOSH approved respirator if exposure limits are exceeded or where dust exposures are excessive. Consider the potential for exposure to components of the coatings or base material being ground in selecting proper respiratory protection. Refer to OSHA's specific standards for lead, cadmium, etc. where appropriate. Selection of respiratory protection depends on the contaminant type, form and concentration. Select and use respirators in accordance with OSHA 1910.134 and good industrial hygiene practice.

Skin protection: Cloth or leather gloves recommended.

Eye Protection: Safety goggles, safety glasses with side shields or face shield over safety glasses with side shields.

Other: Protective clothing as needed to prevent contamination of personal clothing. Hearing protection may be required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): Cloth abrasive products with no odor. Odor: No Odor

Odor threshold: Not applicable	pH: Not applicable			
Melting point/freezing point: Not applicable	Boiling Point: Not applicable			
Flash point: Not applicable	Evaporation rate: Not applicable			
Flammability (solid, gas): Not combustible				
Flammable limits: LEL: Not applicable	UEL: Not applicable			
Vapor pressure: Not applicable	Vapor density:			
Relative density: Not applicable	Solubility(ies): Not soluble			
Partition coefficient: n-octanol/water: Not applicable	Auto-ignition temperature: Not applicable			
Decomposition temperature: Not applicable	Viscosity: Not applicable			

10. STABILITY AND REACTIVITY

Reactivity: Not reactive.

Chemical stability: Stable.

Possibility of hazardous reactions: None known.

Conditions to avoid: None known.

Incompatible materials: None known.

Hazardous decomposition products: Dust from sanding could contain ingredients listed in Section 3 and other, potentially more hazardous components of the base material being ground or coatings applied to the base material.

11. TOXICOLOGICAL INFORMATION

Routes of exposure:

Inhalation: Dust may cause respiratory irritation.

Ingestion: None expected under normal use conditions. Swallowing large pieces may cause obstruction of the gastrointestinal tract.

Skin contact: None expected under normal use conditions. Rubbing product across the skin may cause mechanical irritation or abrasions.

Eye contact: Dust may cause eye irritation. Dust particles may cause abrasive injury to the eyes.

Chronic effects from short- and long-term exposure: Long-term overexposure to respirable dust may cause lung damage (fibrosis) with symptoms of coughing, shortness of breath and diminished breathing capacity. Chronic effects may be aggravated by smoking. Prolonged exposure to elevated noise levels during operations may affect hearing. A greater hazard, in most cases, is the exposure to the dust/fumes from the material or paint/coatings being sanded. Most of the dust generated during sanding is from the base material being sanded and the potential hazard from this exposure must be evaluated.

Carcinogenicity: None of the components are listed as a carcinogen or potential carcinogen by OSHA, NTP or IARC.

Numerical measures of toxicity: This product and its components are not acutely toxic. Silicon Carbide: Oral rat LD50 >2000 mg/kg, Dermal rat LD50 >2000 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity: No data available.
Persistence and degradability: No data available
Bioaccumulative potential: No data available
Mobility in soil: No data available.
Other adverse effects: No hazards to the environment are expected from this product. However, consideration must be given to potential environment effects of the base material being processed.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable local, state/provincial and federal regulations. Local regulations may be more stringent than regional and national requirements. It is the responsibility of the waste generator to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

14. TRANSPORT INFORMATION

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT	None	Not Regulated	None	None	
TDG	None	Not Regulated	None	None	

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions: None identified.

15. REGULATORY INFORMATION

SARA Section 311/312 Hazard Categories: Classified as per Section 2 of this SDS.

SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (Toxic Chemical Release Reporting): None

16. OTHER INFORMATION

NFPA Rating: Health = 1Flammability = 0Instability = 0HMIS Rating: Health = 1Flammability = 0Physical Hazard =0

Date Previous Revision: 3/31/15 Date This Revision: 6/15/18 Revision Summary: 6/15/18: Three year review. Change to Section 3, 8, 15 & 16. 3/31/15: Changed all sections. Updated format to GHS. 5/23/12: Section 8: Exposure Limits; Comprehensive Review The preceding information is believed to be correct and current as of the date of preparation of this Safety Data Sheet. Since the use of this information and the conditions of use of this product are not within the control of United Abrasives, Inc., it is the user's obligation to assure safe use of this product.