


MATERIAL DATA SHEET	PAGE: 1 OF 2
MODEL: 44962B	DATE 25-08-2021

SECTION I. PRODUCT DESCRIPTION

Stringer Bead Wheel Brush, 9" outside diameter , oil tempered carbon steel wire gauge .020", 5/8"-11 threaded nut, JAZ markings and packaging. Maximum safety RPM: 6,000. Recommended working max.RPM:3,600



SECTION II. PHYSICAL DATA AND DIMENSIONS

According to above drawing, 9" diameter, 2" trim length.

N° of knots: 76

N° of .020" wires per knot: 22

Total N° of .020" wire ends in the brush: 3,344

Weight of total product: 900 gr.

SECTION III. CHEMICAL COMPOSITION OF WIRE

Oil Tempered Carbon Steel Wire with following chemical composition:

C = 0,50 – 0,65%

Mn = 0,40 – 0,80%

Si = 0,10 – 0,35 %

There is no special requirements nor standards in the technical brushware industry related to the steel wires used in our products.



MATERIAL DATA SHEET	PAGE: 2 OF 2
MODEL: 44962B	DATE: 25-08-2021

SECTION IV. SAFETY DATA

The European Standard EN 1083-2 about Safety Requirements in the use of Power-driven brushes states the safety instructions that all brush operators must observe. These requirements and common safety practices will reduce the likelihood of physical injury and brush fail:

Wear safety goggles, protective clothing and equipment.

Observe all speed restrictions indicated on the brushes, packaging or catalogue.

And do not exceed Maximum Safe Free Speed (Max. RPM) under any circumstances.

Keep machine guards in place.

Do not use deteriorated brushes

The power tool speed influences the performance of the brush and the safety of the operator. If load speed marked on the power tool is higher than the brush Maximum RPM do not mount brush. Maximum RPM are indicated on brush side-plates and shall never be exceeded. For most brushing applications optimum results are achieved at the Recommended RPM specified in our catalogue for every power driven brush.

Eibar, Spain, August 25th 2021.

**Signed by: OSCAR VAZQUEZ
Manufacturing Director**

**Signed by: AINARA BARRIO
Quality Manager**

